



SAFETY DATA SHEET
W/B Satin Black Enamel

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name W/B Satin Black Enamel

Product number 12993

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial wood coating.

1.3. Details of the supplier of the safety data sheet

Supplier Intercoat Industrial Paints Ltd
Bridgeman Street
Walsall
West Midlands WS2 9NW
01922 638821
01922 722952

1.4. Emergency telephone number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements EUH208 Contains METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6. May produce an allergic reaction.

Precautionary statements P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information EUH210 Safety data sheet available on request.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

BUTYL DI GLYCOL	1-5%
CAS number: 112-34-5	EC number: 203-961-6
Classification	Classification (67/548/EEC or 1999/45/EC)
Eye Irrit. 2 - H319	-

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

W/B Satin Black Enamel

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Chemical storage.

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA): OES 25 ppm(Sk)

Short-term exposure limit (15-minute): OES 50 ppm(Sk)

ETHANOL

Long-term exposure limit (8-hour TWA): OES 1000 ppm 1920 mg/m³

Short-term exposure limit (15-minute): OES

PROPAN-2-OL

W/B Satin Black Enamel

Long-term exposure limit (8-hour TWA): OES 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): OES 500 ppm 1250 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Wear a suitable dust mask.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Liquid.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability

No particular stability concerns.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid

Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

10.6. Hazardous decomposition products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation

No specific health hazards known.

Ingestion

May cause discomfort if swallowed.

Skin contact

No specific health hazards known.

Eye contact

Vapour or spray in the eyes may cause irritation and smarting.

SECTION 12: Ecological Information

Ecotoxicity

Not regarded as dangerous for the environment.

12.1. Toxicity

W/B Satin Black Enamel

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

Road transport notes Not classified.

Rail transport notes Not classified.

Sea transport notes Not classified.

Air transport notes Not classified.

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

Guidance Workplace Exposure Limits EH40.
Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date 01/06/2016

Risk phrases in full Not classified.
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R34 Causes burns.
R36 Irritating to eyes.
R36/38 Irritating to eyes and skin.
R37 Irritating to respiratory system.
R50 Very toxic to aquatic organisms.

W/B Satin Black Enamel

Hazard statements in full

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

EUH208 Contains METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6. May produce an allergic reaction.